

## New Product: Visual Indicators

We are pleased to release a new range of Visual Indicators for flow and level monitoring.

The V25 series Visual Indicators are a new innovative design to separate the liquid from the indicator eliminating many often seen problems as discoloration of the dome and liquids becoming stagnate within the shatter proof super tough dome.

Available in normally green changing to red or normally red changing to green.

The V25F is a flow sensing paddle for small and large piping and is a self-powered magnetically operated insertion indicator for pipes upwards of 1" diameter. The indicator can be normally red and with flow the indicator changes to green. It can be mounted for flows either horizontally or vertically up.

Available in polypropylene rated to 10 bar or stainless steel rated to 200 bar with BSP threads. IP68 rated.

The V25L for tank level monitoring is supplied with a float and arm suitable for installing through the sidewall of a tank. 2 V25L can be installed for low and high liquid levels with red or green indicators. The V25L is a non-electrical insertion style inferential indicator.

The V25L is available in polypropylene or stainless steel construction. A maximum operating pressure of 200 kPa (20 metres submergence), BSP threads and IP68 rated.

Refer to the attached specification sheet for more details.



Description	Order No.	List Price excl GST
V25F-PP-BSP-NR	305 701 241	167.00
V25L-PP-BSP-NR/NG	305 701 243	286.00

These new Visual Indicators will be added into our next Price List update.

In the meantime, your Franklin ASM can assist with any further information.

## 1300 FRANKLIN